

Leica ScanStation P50

Because every detail matters



The right choice

Whether you have to 3D capture the world's tallest buildings, document the widest infrastructure objects or scan the biggest open pit mines, you know long range scanning will be essential for your job. Adding long range scanning capability to the market leading ScanStation P-Series, the Leica ScanStation P50 is the right choice, because every detail matters.



Scan inaccessible places

The ScanStation P50 delivers highest quality 3D data and HDR imaging at an extremely fast scan rate of up to 1 mio points per second and ranges of more than 1 km. Unsurpassed range and angular accuracy paired with low range noise and survey-grade dual-axis compensation form the foundation for highly detailed 3D colour point clouds mapped in realistic clarity.



Complete scanning solution

Leica Geosystems offers the ScanStation P50 as a complete scanning solution including hardware, software, service, training and support. Captured data can be visualised and pre-registered in the field with Cyclone FIELD 360 app or fully registered with Cyclone FIELDWORX app, then processed in the industry's leading 3D point cloud office software suite, comprising Cyclone stand-alone software, JetStream, CloudWorx plug-in tools for CAD systems and the cost-free TruView.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

Leica ScanStation P50 Product Specifications

SYSTEM ACCURACY

Accuracy of single measurement *

Range accuracy	1.2 mm + 10ppm over full range (120 m / 270 m mode) 3 mm + 10ppm over full range (570 m / >1 km mode)
Angular accuracy	8" horizontal; 8" vertical

Target acquisition ** 2mm standard deviation at 50m

Dual-axis compensator Liquid sensor with real-time onboard compensation, selectable on/off, resolution 1", dynamic range ±5', accuracy 1.5"

DISTANCE MEASUREMENT SYSTEM

Type	Ultra-high speed time-of-flight enhanced by Waveform Digitising (WFD) technology	
Wavelength	1550nm (invisible) / 658 nm (visible)	
Laser class	1 (in accordance with IEC 60825:2014)	
Beam divergence	< 0.23 mrad (FWHM, full angle)	
Beam diameter at front window	≤ 3.5 mm (FWHM)	
Range and reflectivity	Minimum range 0.4 m	
	Maximum range mode	Reflectivity
	120 m	8%
	270 m	34%
	570 m	60%
	>1 km	80%

Scan rate Up to 1,000,000 points per second

Range noise * 0.4 mm rms at 10m
0.5 mm rms at 50m

Field-of-View

Horizontal 360°
Vertical 290°

Data storage capacity 256GB internal solid-state drive (SSD) or external USB device

Communications / Data transfer Gigabit Ethernet, integrated Wireless LAN or USB 2.0 device

Onboard display Touchscreen control with stylus, full colour VGA graphic display (640×480 pixels)

Laser plummet Laser class 1 (IEC 60825:2014)
Centring accuracy: 1.5 mm at 1.5 m
Laser dot diameter: 2.5 mm at 1.5 m
Selectable ON/OFF

IMAGING SYSTEM

Internal camera

Resolution 4 MP per each 17°×17° colour image;
700 MP for panoramic image

Pixel size Video 2.2 μm
Streaming video with zoom; auto-adjusts to ambient lighting

White balancing HDR Sunny, cloudy, warm light, cold light, custom Tonemapped / full range

External camera Canon EOS 60D/70D/80D/90D supported

POWER

Power supply	24 V DC, 100 – 240 V AC
Battery type	2× Internal: Li-Ion; External: Li-Ion (connect via external port, simultaneous use, hot swappable)
Duration	Internal > 5.5h (2 batteries) External > 7.5h (room temp.)

ENVIRONMENTAL

Operating temperature	-20°C to +50°C / -4°F to +122°F
Storage temperature	-40°C to +70°C / -40°F to +158°F
Humidity	95%, non-condensing
Dust/Water	Solid particle/liquid ingress protection IP54 (IEC 60529)

PHYSICAL

Scanner	
Dimensions (D×W×H)	238 mm × 358 mm × 395 mm / 9.4" × 14.1" × 15.6"
Weight	12.25 kg / 27.0 lbs, nominal (w/o batteries)
Battery (internal)	
Dimensions (D×W×H)	40 mm × 72 mm × 77 mm / 1.6" × 2.8" × 3.0"
Weight	0.4 kg / 0.9 lbs
Mounting	Upright or inverted

CONTROL OPTIONS

Full colour touchscreen for onboard scan control.
Remote control: Leica CS10/CS15/CS20/CS35 controller or any other remote desktop capable device, including iPad, iPhone and other Smartphones; external simulator.
Leica Cyclone FIELD 360 with tablet and Smartphone (iOS and Android).
Leica Cyclone FIELDWORX with Windows® Surface tablet.

FUNCTIONALITY

Survey workflows and onboard registration	Quick orientation, Set azimuth, Known backsight, Resection (4 and 6 parameters), Traverse
Check & Adjust	Field procedure for checking of angular parameters, tilt compensator and range offset
Onboard target acquisition	Target selection from video, scan or red laser beam
Onboard user interface	Switchable from standard to advanced
One button scan control	Scanner operation with one button concept
Scan area definition	Scan area selection from video or scan; batch job scanning
Double scan	Automatic removal of point cloud noise introduced by moving objects

All specifications are subject to change without notice.
All accuracy specifications are one sigma unless otherwise noted.

* At 78% albedo

** Algorithmic fit to planar HDS 4.5" B&W targets

Scanner: Laser class 1 in accordance with IEC 60825:2014
Laser plummet: Laser class 1 in accordance with IEC 60825:2014

iPhone and iPad are trademarks of Apple Inc.

Microsoft, Windows® and the Windows logo are either registered trademarks or trademarks of Microsoft Corporation in the United States and / or other countries.

Illustrations, descriptions and technical specifications are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland 2017. 869145en - 12.20

active >>
Customer Care

Your Trusted Active Customer Care


Active Customer care is a true partnership between Leica Geosystems and its customers. Customer Care Packages (CCPs) ensure optimally maintained equipment and the most up-to-date software to deliver the best results for your business. The myWorld@Leica Geosystems customer portal provides a wealth of information 24/7.

Leica Geosystems AG

Heinrich-Wild-Strasse
9435 Heerbrugg, Switzerland
+41 71 727 31 31



Leica ScanStation
P30/P40



Leica RTC360
3D Reality Capture
Solution



Leica Cyclone
REGISTER 360

- when it has to be **right**

Leica
Geosystems